



10/520501
J12 Rec'd POT/PTO 04 JAN 2005



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 2006 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

accordance with the rules, the words "public limited company" may be replaced by p.l.c., L.L.C. or PLC.

Registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

CERTIFIED COPY OF PRIORITY DOCUMENT

Signed

Andrew Gershey

Dated

4 November 2004


PRIORITY DOCUMENT

The
Patent
Office

1/77
RECEIVED 1 JUL 2002
0215697.4

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference

P 100488GB

2. Patent application number

(The Patent Office will fill in this part)

0215697.4

6 JUL 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

The BOC Group plc
Chertsey Road
Windlesham
Surrey GU20 6HJ
UK

Patents ADP number (if you know it)

797594901

If the applicant is a corporate body, give the country/state of its incorporation

England

4. Title of the invention

Fluorine Cell

5. Name of your agent (if you have one)

Harrison Goddard Foote

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)
Orlando House
11c Compstall Road
Marple Bridge
Stockport SK6 5HH
UK

Patents ADP number (if you know it)

14571002

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

Yes

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 11 ✓
Claim(s) 3 ✓
Abstract 1 ✓
Drawing(s) 3 + 3

OK

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) 1 ✓

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

Covering letter with fee sheet and cheque ✓

11.

I/We request the grant of a patent on the basis of this application.

Hamilton Goddard Foote Signature

Date
05 July 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

David Goddard

0161 427 7005

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

P100488GB

FLUORINE CELL

- 5 The present invention relates to the construction of fluorine cells and particularly to the construction relating to the closing of the anode connection to the fluorine producing compartment in such a cell.
- 10 Fluorine generating cells produce both gaseous fluorine and hydrogen by the electrolysis of hydrogen fluoride. Fluorine and hydrogen explosively recombine when they contact each other, therefore, it is necessary to keep them completely separate when generated during
- 15 electrolysis. Fluorine cells are generally constructed such that the two gases are collected in two separate compartments above the surface level of the electrolyte. The compartments are often separated by means of a so-called skirt, the skirt often being part of and depending
- 20 from an upper, generally horizontal wall of the cell, and extending into the electrolyte and surrounding the anode. However, the skirt must remain electrically neutral with respect to the anode which it surrounds and to the cathode which is often formed by the inner wall of the
- 25 cell container vessel. It is, therefore, necessary that the skirt is electrically insulated from the anode (and cathode) and for the anode connection (often referred to as the "stud") to pass through the skirt or be connected thereto whilst completely sealing the fluorine
- 30 compartment against leakage of fluorine.

It has been the practice to have a stud for connection to the anode and which stud passes through an insulating member, often made of plastics material such as a

fluoroelastomer rubber, in the skirt wall. However, due to the high currents which are inherent in fluorine generation by electrolysis a considerable amount of heat is generated by resistance heating, this condition often
5 being exacerbated by poor electrical connection between the stud and carbon anode which is generally used. The effect of this heating can be to cause a runaway chemical reaction between the plastics seal material and the fluorine which may result in a fluorine leak. In extreme
10 cases even the stud metal may itself burn in the fluorine gas stream in the resulting leak causing a so-called "stud fire". This has been somewhat alleviated by the construction shown in WO 96/08589 where, instead of the anode connecting stud passing through an insulating seal
15 in the skirt wall, the stud is formed by welding stud members on either side of the skirt wall, so that there is no through hole, and closing the fluorine compartment by an insulating gasket remote from the anode stud. However, even in this construction, whilst an improvement
20 on earlier constructions, the sealing gasket is still directly contacted by the fluorine gas and is still susceptible to attack especially when there is an unexpected temperature rise for any reason.

25 According to a first aspect of the present invention, there is provided an arrangement for sealing an anode within a fluorine generating electrolytic cell, the arrangement comprising: an anode connection member, said anode connection member passing through an aperture in a
30 skirt wall and being in electrical connection with a skirt wall closure member wherein the skirt wall closure member is sealingly engaged with said skirt wall to seal said aperture and is electrically insulated therefrom.

In a preferred embodiment of the present invention the skirt wall closure member is sealingly engaged with the skirt wall around the aperture and electrically insulated from the skirt wall by means of an electrically non-conductive member such as, for example, a ceramic spacer member. The spacer member may surround the anode connection member. The spacer member is essentially non-porous in the sense that there is no significant interconnected porosity which allows the passage of unacceptable quantities of fluorine gas to diffuse therethrough.

Examples of ceramic materials which may be utilised include alumina, calcium fluoride and magnesium fluoride. The material of the spacer member must be resistant to the effects of fluorine gas.

In one embodiment of the arrangement of the present invention, the ceramic spacer is of annular form with flat, sealing faces and surrounds both the aperture through which the anode connection member extends and the anode connection member itself.

It is further preferred that the ceramic spacer member is sandwiched between two gaskets, one on each radial face thereof. In a preferred embodiment of the arrangement of the present invention the gaskets are so-called spiral wound gaskets which are supplied by many different manufacturers. Spiral wound gaskets comprise a spiral winding of a strip of at least one material which may be of "V" shaped cross section and known as the winding element. Frequently, there is a second element of similar cross sectional shape known as a sealing element, the two strips being nestled together and wound together so as to form alternate elements when viewed in cross section. The

winding element is generally a metal which can be any metal of sufficient ductility and in any suitable metallurgical condition, e.g. annealed or cold worked, for example, and compatible with fluorine such as stainless steel or nickel, for example. The sealing element strip may be of a non-metallic material such as PTFE, expanded graphite or asbestos, for example, or may be of another, softer metal such as copper, for example. The spiral wound portion of the gasket may have inner and/or outer keeper rings to prevent the spiral wound portion from unwinding.

Where spiral wound gaskets having metallic elements in their construction are employed, the ceramic spacer member is necessary to provide electrical insulation of the anode from the skirt wall to render the latter electrically neutral.

In the present invention where, for example, the sealing element strip may be PTFE for example, because of the geometry of the gasket only a very small area of PTFE is exposed to the fluorine gas. However, spiral wound gaskets of fluorine-resistant all metal construction may be employed.

Such spiral wound gaskets as are contemplated in the present invention are by their nature generally of annular shape and construction and their size may be chosen to suit the radial face dimensions of the insulating spacer member.

The anode connection member may be welded to the inner surface of the skirt wall closure member. However, for reasons of dimensional accuracy, it is preferred that the anode connection member is a machined member which is

attached to the skirt wall closure member by mechanical fasteners so that it and the anode may be easily removed for repair or maintenance. Such a construction generally requires that through holes be made in the skirt wall closure member and fasteners such as screws for example pass through holes to locate in suitable receiving holes in the anode connection member. It is possible to provide the fastening means with washers which seal against egress or leakage of fluorine through the fastener location holes via co-operating screw threads for example. However, in the interests of safety it is preferred that the anode fastening means may themselves be sealed from the ambient atmosphere with an auxiliary closure member which is sealed to the skirt wall closure member by means of a further gasket which surrounds the anode connection member fastening means. Such a further gasket may also advantageously comprise a spiral wound gasket.

Whilst spiral wound gaskets have proved to be exceptionally effective in the sealing arrangement of the present invention other types of gasket made from sheet metal such as copper, for example, may be used in the form of embossed bead gaskets where elongate beads surrounding portions to be sealed are embossed into a metal sheet and which beads are then compressed during assembly to provide a seal.

The anode connection member may be for connecting to a separate anode such as a carbon anode by any known means or may itself be integrally formed with an anode portion which is adapted to be at least partially immersed in an electrolyte in the cell.

According to a second aspect of the present invention, there is provided a method of sealingly installing an anode in a fluorine generating electrolytic cell, the method comprising the steps of: providing a skirt member
5 for a fluorine generating electrolytic cell, the skirt member being of open-ended construction which, when in use, a lower extremity of said open end is immersed in an electrolyte and forms a closed volume; forming an aperture in said skirt member to permit an anode
10 connection member to pass through; suspending said anode connection member from a skirt wall closure member and sealing said aperture with said skirt wall closure member by providing at least one sealing, non-electrically conductive member therebetween.

15

As described hereinabove, the at least one sealing, non-electrically conductive member may comprise a ceramic spacer member which is electrically non-conductive. In the interests of safety further sealing may be effected
20 by suitable gaskets such as spiral wound gaskets, for example, preferably on each radial face of said spacer member.

The skirt wall, skirt wall closure member and auxiliary
25 closure member, where fitted, may be held together by conventional mechanical fastening means such as threaded studs, nuts and bolts and the like. The materials from which the constituent parts of the anode sealing arrangement may be made are those known and used in the
30 fluorine generating art.

According to a third aspect of the present invention there is provided a fluorine generating cell having the anode sealing arrangement of the first aspect.

35

In order that the present invention may be more fully understood, examples will now be described by way of illustration only with reference to the accompanying drawings, of which:

5

Figure 1 shows an elevation in cross section of a schematic electrolytic fluorine generating cell having the arrangement of anode installation according to the present invention;

10

Figure 2 shows the arrangement of anode sealing installation of Figure 1 at a larger scale; and

Figure 3 which shows a plan view of the arrangement of
15 Figures 1 and 2 in the direction of arrow 3 of Figure 2

Referring now to the drawings and where the same features are denoted by common reference numerals.

20 Figure 1 shows an elevation in part cross section of a schematic electrolytic fluorine generating cell 10 having an anode sealing arrangement 12 according to the present invention. Most of the cell is conventional and is only shown and described to place the anode sealing
25 arrangement of the present invention in context.

The cell 10 includes an outer cell vessel 14 which also forms the cathode 16 and contains the electrolyte 18; a skirt member 20 which comprises a generally horizontal
30 top plate 22 and a depending gas separating skirt member 24 which extends below the surface 26 of the electrolyte 18 and completely encircles an anode 30 and anode connection member 32; and, an anode sealing arrangement 12, in this case according to the present invention. The
35 construction of the cell forms two separate compartments

40, 42, each closed at the lower end by the electrolyte surface 26, and which compartments receive hydrogen and fluorine, respectively upon electrolysis of the electrolyte 18 on passing a current therethrough. Outlet
5 conduits 44 and 46 having valve means 48, 50 to control the flow of gas are provided for the two compartments. The anode sealing installation 12 according to the present invention also provides the anode connection 56. A heating jacket (not shown) is normally provided around
10 the cell vessel 14 in order to melt the electrolyte which is normally solid at ambient temperature; the heating jacket may comprise a steam jacket or an electrically heated blanket for example. A plate 58, usually of a non-electrically conductive plastics material is fixed to the
15 cell bottom to prevent hydrogen from being formed on the cathodic area below the anode compartment 42 and consequently rising into the fluorine compartment 42 and explosively recombining with the fluorine. The skirt 20 is electrically neutral being insulated from the cathodic
20 vessel 14 by an insulating gasket 60 and from the anode sealing installation 12 by means which will be described in greater detail below.

Referring now to Figures 2 and 3 where the anode sealing
25 installation according to the present invention is shown in more detail. The sealing arrangement 12 of Figure 2 is a section along the line 2-2 of Figure 3. The anode connection member is ultimately connected to the anode 30 which is at least partially immersed in the electrolyte 18 as shown in Figure 1, however, neither the anode nor its construction per se form any part of the invention and may be of any suitable construction or material according to the type of fluorine cell in which it is to be used. The anode connection member 32 (shown truncated
30 in Figure 2) passes through an aperture 70 in the
35

horizontal top plate 22 of the skirt member 20. The anode connection member 32 is fixed to a skirt wall closure member 72 by means of screws 74 passing through holes 76 into threaded holes 78 in a boss 80 of the connection member 32, however, any means of connection of the member 32 to the closure member 72 may be employed. The arrangement described provides accuracy for the depending anode 30 in maintaining the anode 30 out of contact with the depending skirt wall member 24, but providing that accuracy can be assured, the connection member 30 may be welded, for example, to the underside 82 of the closure member 72. Alternatively, the end of the connection member 32 may be provided with a screw thread and screwed into a co-operating hole in the closure member 72, for example. The closure member 72 is insulated from the skirt 20 by a non-conductive annular spacer ring 90 which is positioned intermediate two annular gaskets 92. In this case the gaskets are spiral wound gaskets having inner keeper rings 94 and outer keeper rings 96. Whilst the gaskets 92 are electrically conductive they are separated by the non-conductive spacer ring 90 which, in this case, is made of non-porous alumina ceramic. The spacer ring 90 and gaskets 92 provide complete sealing against leakage of fluorine and the spacer ring 90 provides electrical insulation of the anode 30 from the skirt 20. However, the existence of the holes 76 may provide a potential path for fluorine leakage and in the interests of safety an auxiliary closure member 100 is provided which is itself sealed to the closure member 72 by means of a further spiral wound gasket 102. A recess 104 is provided in the auxiliary closure member 100 to accommodate the heads of the screws 74. The auxiliary closure member 100, the closure member 72, the spacer ring 90, gaskets 92 and 102 are all held together by means of threaded studs 108 and nuts 110. The studs are

insulated from the closure member 72 and auxiliary closure member 100 by insulating sleeves 112, in this case of Mylar (trade name) material, extending along the length thereof and the nuts 110 are insulated from the auxiliary closure member top face 114 by insulating washers 116, in this case, of phenolic material. The spacer ring 90 and gaskets 92, 102 all lie within a pitch circle 120 defining the axes of the studs 108 and, of course, within a circle 122 defining the innermost extent of the stud 108 diameters thus, the insulating sleeves 112 and washers 116 are not subject to contact with fluorine. An electrical connector 56 is provided for a positive connection to the anode from a power source and controller (both not shown).

15

In the embodiment shown the auxiliary closure member 100 is used due the fact that there are through holes 76 in the closure member 72 for securing the anode connection member 32 thereto and which could possibly be a source of fluorine leakage. However, if a construction is employed where no through holes are provided in the closure member 72 for securing the connection member 32 thereto, the auxiliary closure member 100 would not be required.

25 In the embodiment described spiral wound gaskets have been used to seal the faces of the spacer ring 90 and the corresponding faces of the skirt top plate, closure member and auxiliary closure member. The construction of such gaskets is well known in the prior art and they are particularly suitable when used in the present invention. However, other types of metal gaskets may be used such as embossed bead gaskets where beads are embossed into an essentially flat metal plate and sealing is achieved by compression of the beads by the tightening loads.

35

The present invention effectively seals the fluorine compartment of the fluorine cell without the need to place large areas of polymer gasket materials in contact with fluorine and thus the risk of degradation causing fluorine leaks and the possibility of stud fires is greatly reduced compared with prior art sealing methods.

In the embodiment shown and described, the anode connection member 32 is further provided with a hole 130 to permit insertion of a retaining bar (not shown) therethrough for use when servicing or repairing the fluorine cell. When the anode sealing installation 12 is disassembled for servicing etc. the anode assembly may be lifted before removal of the closure member 72, a bar inserted in the hole 130 and rested across the skirt top face 22 to prevent the anode 30 from dropping into the vessel bottom.

In another embodiment of the present invention, the anode connection member may be at least partially formed as an integral part of the closure member 72, e.g. as a spigot depending from the inner central part thereof and the anode joined thereto, for example, by an internally threaded collar co-operating with threaded ends on the anode connection portion at the upper end and a threaded end on a rod connected to an anode hanger at the lower end. Thus, in this embodiment the auxiliary closure member would not be required. Furthermore, the closure member and the anode connection member are a unitary item.

CLAIMS

1. An arrangement for installing and sealing an anode within a fluorine generating electrolytic cell, the arrangement comprising: an anode connection member, said anode connection member passing through an aperture in a skirt wall of the fluorine cell and being in electrical connection with a skirt wall closure member wherein the skirt wall closure member is sealingly engaged with said skirt wall to seal said aperture and is electrically insulated therefrom.
2. An anode sealing arrangement according to claim 1 wherein a non-conductive spacer member is interposed between the closure member and the skirt wall.
3. An anode sealing arrangement according to claim 2 wherein the spacer member is made of a ceramic.
4. An anode sealing arrangement according to claim 3 wherein the ceramic is selected from the group comprising: alumina, calcium fluoride and magnesium fluoride.
5. An anode sealing arrangement according to any one of preceding claims 2 to 4 wherein the spacer is of annular form and surrounds both the aperture through which the anode connection member extends and the anode connection member itself.
6. An anode sealing arrangement according to any one of preceding claims 2 to 5 wherein the spacer member is sandwiched between two gaskets.
7. An anode sealing arrangement according to claim 6 wherein the gaskets are spiral wound gaskets.
8. An anode sealing arrangement according to any one of preceding claims 2 to 6 wherein the gaskets are metal bead gaskets.


9. An anode sealing arrangement according to claim 8 wherein the gaskets comprise a metal plate having a bead embossed therein.
10. An anode sealing arrangement according to claim 7 wherein the spiral wound gaskets are provided with inner and/or outer keeper rings.
11. An anode sealing arrangement according to any one preceding claim wherein the anode connection member is welded to the closure member.
12. An anode sealing arrangement according to any one preceding claim from 1 to 10 wherein the anode connection member is attached to the skirt wall closure member by mechanical fastening means, the arrangement further including an auxiliary closure member which is sealed to the skirt wall closure member by means of a further gasket which surrounds the anode connection member fastening means.
13. An anode sealing arrangement according to claim 12 wherein the gasket is a spiral wound gasket.
14. A method of sealingly installing an anode in a fluorine generating electrolytic cell, the method comprising the steps of: providing a skirt member for a fluorine generating electrolytic cell, the skirt member being of open-ended construction which, when in use, a lower extremity of said open end is immersed in an electrolyte and forms a closed volume; forming an aperture in said skirt member to permit an anode connection member to pass through; suspending said anode connection member from a skirt wall closure member and sealing said aperture with said skirt wall closure member by providing at least one sealing, non-electrically conductive member therebetween.
15. A fluorine generating cell having the anode sealing arrangement of any one of preceding claims 1 to 13.

16. A fluorine generating cell having an anode sealing arrangement when made by the method of claim 14.
17. An arrangement for the installation and sealing of an anode in a fluorine generating electrolytic cell substantially as hereinbefore described with reference to the accompanying description and Figures 1 to 3 of the drawings.
18. A method of sealingly installing an anode in a fluorine generating electrolytic cell substantially as hereinbefore described with reference to the accompanying description and Figures 1 to 3 of the drawings.

ABSTRACT

An arrangement for installing and sealing an anode within
5 a fluorine generating electrolytic cell is described, the
arrangement comprising: an anode connection member, said
anode connection member passing through an aperture in a
skirt wall and being in electrical connection with a
skirt wall closure member wherein the skirt wall closure
10 member is sealingly engaged with said skirt wall and is
electrically insulated therefrom.

Fig. 1






Fig. 2




Fig. 3.